

Product Finish: Chrome


# **PROFILE 3 Part Mixer**

Product code: PT1007 EAN13 barcode: 5060344152983

# **Product features:**

- Stylish 4 way mixer tap delivering domestic hot and cold, ambient and 80-98° filtered water.
- Suppled with 2 x patent pending proximity Hotkey™ activation for 80-98° water, without the Hotkey™ the product reverts to a family safe 3 way mixer.
- 360° rotating thermally insulated spout
- Ceramic disc 1/4 turn smooth action control valves
- Hands free dispensing of 80-98° water possible for heavy pans
- Anti splash aerator as standard

### **Product dimensions:**



Overall Height / projection: 368 mm

• Exit reach: 216 mm • Exit height: 240 mm

• Centre distance(s): 90 - 180


• Base diameter(s): 45 x 45 x 45 mm • Recommended hole diameter: Ø35 mm

• Max. surface depth: 50 mm

• Spout diameter: 24 mm

• Spout aerator size: M22x1 Male

### **Product flow characteristics:**



- Min / Max water pressure: 0.75 / 5.5 bar (mixertap only)
- Recommended / Max incoming domestic hot water temperature: 46°C / 70°C
- Part G Mixed flow rate at 3 bar (litres / min): 9.97
- Control valve type: 1 x Ceramic disc QT hot, 1 x Diverter Cold/Filter
- Product flow characteristics: (C,H&F/Boiling) dual flow
- · Aerator type: Neoperl aerator honeycomb dual flow
- Hot and Cold inlet connections: M10 x 1/2" M x 365mm flexi hose
- Non return valve(s): Yes, integral to hot and cold supplies

- Clean the product regularly as required, using a mild soap and damp cloth, do not use any other cleaners, regular cleaning will prevent the build-up of lime scale and dirt Residues of sink & worktop cleaners can also cause damage to the mixer tap, so rinse with clean water after using, avoid contact with any abrasives

### Warranty Summary (Full details available on request):

- Mixer tap Materials and workmanship defects warranted for 5 years
- Proboil3 Materials and workmanship defects warranted for 2 years Mixer tap Valves and working parts warranted for 5 years
- Surface finish warranty defects warranted for 1 year
- All o-rings, hoses & gaskets warranted for 1 year



\*All temperatures quoted are measured within the tank of the boiler and actual spout exit temperature may vary dependant on local conditions.

### PROBOIL3 features:

- 80-98°C variable stored water temperature
- 3.5 litres maximum continuous draw off
- 50 cups per hour recovery rate
- Electronically controlled hot water system to ensure the first cup to the last are equally hot.
- Pumped delivery to ensure smooth flow with no spitting
- High quality stainless steel tank construction
- UK manufactured
- Choice of energy saving Eco modes
- Choice of 9 languages
- On screen service notifications with QR code links to user 'how to' maintenance videos
- Filter status indicator bar
- Child lock function
- Intelligent descale notification, user drainable & descalable
- Dimensions: 175mm (w) x 400mm (d) x 410mm (h)
- Weight (when full): 12.5Kg
- Power rating: 2.8kW, 220-240V 50Hz, 13A
- Pressure rating (min max): 2-8 bar
- Boiler approvals: BS EN 60335-2-75:2004 +A2:2008, LVD (2014/35/EU), EMC (2014/30/EU), CE (93/68/EEC), RoHS(2011/65/EU)

For further information refer to proboil.co.uk and our user guides.



Our premium quality **PRO**BOIL filter offers the following benefits:

- Filtered ambient and 80-98°C drinking water, engineered specifically for hot and ambient water applications
- Included with every PROBOIL system
- 6 month life (based on 19 degrees Clark (London average hardness) and 5 litres per day usage)
- Superfine 5 micron carbon block filtration
- Chlorine taste and odour reduction.
- pH balanced delivery
- Adjustable hardness settings allows optimised filter life and boiler scale protection
- Inbuilt corrosion protection
- Mineral adaption and scale reduction for protection
- Simple quarter turn bayonet installation
- Automated on screen life reminder



## The complete package:

Each **PRO**NTEAU system includes:

- A stylish choice of intelligent 4 way **PRONT**EAU mixer taps
- 2 x 4 way mixer tap Hotkeys
- PROBOIL3 boiler
- PROBOIL premium scale filter and head
- Connecting hoses, safety devices and plumbing sundries
- Comprehensive installer and user guides
- User draining kit
- Nationwide professional installation service available on request
- Nationwide professional maintenance and service support
- Extended warranties and service plans available on request